


موتورهای زاویه محدود بدون ذغال

BLDC LIMITED ANGLE TORQUE MOTOR



MODEL: LA-4915-45		PRODUCT SPECS.	
PARAMETER	SYMBOL	UNIT	VALUE
PEAK TORQUE, STALLED @VP	T_p	mNm	200
COGGING TORQUE	T_{CG}	mNm	0
DC RESISTANCE	R	Ω	$11.5 \pm 10\%$
INDUCTANCE	L	mH	$3.5 \pm 10\%$
TORQUE SENSITIVITY	K_{TS}	mNm/A	100
BACK EMF CONSTANT	K_{BE}	mV/(rad/sec)	$88 \pm 10\%$
PEAK VOLTAGE	V_p	V	24
CURRENT @TP	I_p	A	2
INPUT POWER @TP	P	W	48
MOTOR CONSTANT	K_M	mNm/(W) ^{0.5}	29
ROTOR INERTIA	J_M	g.cm ²	61
ANGULAR EXCURSION	D_{AE}	deg	± 45
TEMPERATURE	t	°C	-40 ~ +100
NO. OF POLES			4
BODY COLOR			RED
WEIGHT	m	g	$120 \pm 5\%$



BLDC LIMITED ANGLE TORQUE MOTOR

MODEL: LA-4915-45

